

ServMax X-1208

1U application server with dual Intel 4th/5th Gen Xeon® Scalable processors



Features

- Dual 5th/4th Gen Intel® Xeon® Scalable processors
- Support 1x double-slot or 3x single-slot GPU
- 32 DIMM slots supporting up to 8TB of DDR5-4400 memory
- 2x PCIe 5.0 x16 FHFL; 1x PCIe 5.0 x16 FHHL
- Up to 12x 2.5" hot-swap NVMe/SATA/SAS drive bays

System Specifications

CPU	<ul style="list-style-type: none"> • Dual 4th/5th Gen Intel® Xeon® Scalable processors Supports
Memory	<ul style="list-style-type: none"> • 32 DIMM slots supporting max 8TB DDR5-4400
GPU	<ul style="list-style-type: none"> • 1x double-slot or 3x single-slot GPU
Networking	<ul style="list-style-type: none"> • Flexible options supporting dual or quad NIC from 1G to 100G
Storage	<ul style="list-style-type: none"> • 12x 2.5" hot-swap NVMe/SATA/SAS drive bays • 2x M.2 NVMe (2280/2210) OR 2x M.2 SATA3
Expansion Slots	<ul style="list-style-type: none"> • 2x PCIe 5.0 x16 FHFL • 1x PCIe 5.0 x16 FHHL
I/O	<ul style="list-style-type: none"> • 1x RJ45 Dedicated IPMI LAN port • 1x USB 3.0 ports • 2x USB 2.0 ports • 1 VGA port
BIOS	<ul style="list-style-type: none"> • AMI 64MB SPI Flash
Operating Environment	<ul style="list-style-type: none"> • Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) • Non-operating Temperature: -40°C to 70°C (-40°F to 158°F) • Operating Relative Humidity: 8% to 90% (non-condensing) • Non-operating Relative Humidity: 5% to 95% (non-condensing)
Power Supply	<ul style="list-style-type: none"> • 2x 1200W Redundant Titanium Level power supplies
Fan	<ul style="list-style-type: none"> • 8x 4cm heavy duty fans with optimal fan speed control
Dimensions	<ul style="list-style-type: none"> • WxHxD - 437 x 43 x 747mm (17.2" x 1.7" x 29.4")

