

ServMax X-1224

1U application server with dual Intel 4th/5th Gen Xeon® Scalable processors



Features

- Dual 5th/4th Gen Intel® Xeon® Scalable processors
- 16 DIMM slots supporting up to 4TB of DDR5-5600
 memory
- 2x PCIe 5.0 x16 FHFL
- Up to 4x 3.5"/2.5" hot-swap NVMe/SATA/SAS drive bays

Specifications	
CPU	Dual 4th/5th Gen Intel® Xeon® Scalable processors Supports
GPU	• Up to 2x single-slot
Memory	• 16 DIMM slots supporting max 4TB DDR5-5600
Networking	Support AIOM Network Card
Storage	 6x 2.5" hot-swap NVMe/SATA/SAS drive bays 2x M.2 NVMe (2280)
Expansion Slots	• 2x PCle 5.0 x16 FHFL slot(s)
Ю	 1x RJ45 Dedicated IPMI LAN port 2x USB 3.0 ports 1 VGA port
BIOS	• AMI 32MB SPI Flash
Operating Environment	 Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)
Power Supply	4x 860W Redundant Titanium Level power supplies
Fan	6x 4cm heavy duty fans with optimal fan speed control
Dimensions	• WxHxD - 437 x 43 x 650mm (17.2" x 1.7" x 25.6")



AMAX | 1565 Reliance Way, Fremont, CA 94539 | 1 (800) 800-6328 | www.amax.com | info@amax.com

Copyright © 2024 AMAX. All rights reserved. All trademarks are the property of their respective owners. Technical information is subject to change without notice. All company and product names are trademarks or registered trademarks of their respective owners. v1-2024